

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application.

1. (Previously presented) A method for releasing a communication session involving network entities including session endpoints and intermediary network entities that provide call session control, comprising:

 subscribing one or more of the network entities as subscribers to one or more of the intermediary network entities serving as notifiers;

 making a determination independently of the session endpoints to release the communication session at a first one of the notifiers;

 releasing the communication session at the first notifier;

 initiating a session release notification via a signaling protocol from the first notifier to its respective subscriber;

 logically advancing the session release notification towards a remote one of the session endpoints via the intermediary network entities; and

 terminating the communication session at each of the network entities receiving the session release notification.

2. (Original) The method as in Claim 1, wherein the signaling protocol comprises a Session Initiation Protocol (SIP), and wherein the intermediary network entities comprise Call Session Control Functions (CSCFs) in an IP Multimedia core network Subsystem (IMS).

3. (Original) The method as in Claim 1, wherein initiating a session release notification comprises generating the session release notification in conformance with the signaling protocol, and wherein logically advancing the session release notification comprises passing the session release notification to the remote session endpoint by way of the intermediary network entities.

4. (Original) The method as in Claim 3, wherein the first notifier comprises a Proxy Call Session Control Function (P-CSCF) in an IP Multimedia core network Subsystem (IMS).
5. (Original) The method as in Claim 3, wherein passing the session release notification to the remote session endpoint by way of the intermediary network entities comprises forwarding the session release notification from one intermediary network entity to another intermediary network entity until reaching the remote session endpoint.
6. (Original) The method as in Claim 1, wherein initiating a session release notification comprises generating a first session release notification in conformance with the signaling protocol, and wherein logically advancing the session release notification comprises:
- sending the first session release notification to the subscriber of the first notifier, wherein the subscriber of the first notifier serves as a second notifier to the remote one of the session endpoints; and
 - generating a second session release notification at the second notifier, and passing the second session release notification to the remote session endpoint by way of the intermediary network entities.
7. (Original) The method as in Claim 6, wherein the first notifier comprises a Serving Call Session Control Function (S-CSCF), and the second notifier comprises a Proxy Call Session Control Function (P-CSCF), in an IP Multimedia core network Subsystem (IMS).
8. (Original) The method as in Claim 1, wherein terminating the communication session at each of the network entities comprises treating the session release notification as a session termination message in conformance with the signaling protocol at each of the network entities receiving the session release notification.
9. (Previously presented) The method as in Claim 8, further comprising issuing a session termination message at the remote session endpoint towards at least one other session

endpoint in response to receiving the session release notification and before terminating the communication session at the remote session endpoint.

10. (Original) The method as in Claim 1, wherein subscribing one or more of the network entities as subscribers comprises subscribing in conformance with the signaling protocol.

11. (Original) The method as in Claim 10, wherein subscribing in conformance with the signaling protocol comprises subscribing via a Session Initiation Protocol (SIP).

12. (Original) The method as in Claim 1, wherein the signaling protocol comprises an end-to-end signaling protocol.

13. (Original) The method as in Claim 12, wherein the end-to-end signaling protocol comprises a Session Initiation Protocol (SIP), and wherein the intermediary network entities comprise Call Session Control Functions (CSCFs) in an IP Multimedia core network Subsystem (IMS).

14. (Original) The method as in Claim 1, wherein at least one of the network entities serves as both a subscriber and a notifier.

15. (Original) A method for releasing a dialog established over an IP Multimedia core network Subsystem (IMS) that supports services via the Session Initiation Protocol (SIP), wherein the IMS includes a plurality of Call Session Control Functions (CSCFs) including at least a Proxy CSCF (P-CSCF) and a Serving CSCF (S-CSCF) associated with each User Equipment (UE) involved in the dialog, the method comprising:

initiating the dialog from one UE towards another UE;

subscribing each P-CSCF associated with the dialog to its respective S-CSCF, and

subscribing each of the UEs to the P-CSCF associated with the other UE;

generating a SIP session release notification at one of the CSCFs associated with a release of the dialog and transmitting the SIP session release notification towards its subscriber; and

releasing a dialog state at the remaining CSCFs as a result of the generation and transmission of the SIP session release notification.

16. (Original) The method as in Claim 15, further comprising releasing the dialog state at at least one of the UEs as a result of the generation and transmission of the SIP session release notification.

17. (Original) The method as in Claim 15, wherein the CSCF associated with the release of the dialog comprises a first one of the S-CSCFs, and wherein generating a SIP session release notification at the first S-CSCF comprises generating a SIP NOTIFY message and transmitting the SIP NOTIFY message towards a corresponding first P-CSCF that subscribed to the first S-CSCF.

18. (Original) The method as in Claim 17, wherein releasing a dialog state at the remaining CSCFs comprises:

generating a second SIP NOTIFY message at the first P-CSCF, and transmitting the second SIP NOTIFY message towards the UE that subscribed to the first P-CSCF; and

releasing the dialog state at the remaining S-CSCFs and P-CSCFs in a path from the first P-CSCF towards the UE that subscribed to the first P-CSCF.

19. (Original) The method as in Claim 18, wherein releasing the dialog state at the remaining S-CSCFs and P-CSCFs comprises treating the second SIP NOTIFY message as a SIP BYE at each of the remaining S-CSCFs and P-CSCFs.

20. (Original) The method as in Claim 18, further comprising receiving the second SIP NOTIFY message at the UE that subscribed to the first P-CSCF, and transmitting a SIP BYE message from the UE that subscribed to the first P-CSCF towards the other UE.

21. (Original) The method as in Claim 20, further comprising releasing the dialog state at the UE receiving the SIP BYE message.

22. (Original) The method as in Claim 15, wherein the CSCF associated with the release of the dialog comprises a first one of the P-CSCFs, and wherein generating a SIP session release notification at the first P-CSCF comprises generating a SIP NOTIFY message and transmitting the SIP NOTIFY message towards the UE that subscribed to the first P-CSCF.

23. (Original) The method as in Claim 22, wherein releasing a dialog state at the remaining CSCFs comprises releasing the dialog state at the remaining S-CSCFs and P-CSCFs in a path from the first P-CSCF towards the UE that subscribed to the first P-CSCF.

24. (Original) The method as in Claim 23, further comprising receiving the SIP NOTIFY message at the UE that subscribed to the first P-CSCF, and transmitting a SIP BYE message from the UE that subscribed to the first P-CSCF towards the other UE.

25. (Original) The method as in Claim 24, further comprising releasing the dialog state at the UE receiving the SIP BYE message.

26. (Original) The method as in Claim 23, wherein releasing the dialog state at the remaining S-CSCFs and P-CSCFs comprises treating the second SIP NOTIFY message as a SIP BYE at each of the remaining S-CSCFs and P-CSCFs.

27. (Original) The method as in Claim 15, further comprising subscribing a first P-CSCF associated with a non-compliant UE with a second P-CSCF associated with the other UE.

28. (Original) The method as in Claim 15, wherein the SIP session release notification comprises a SIP NOTIFY message including a state indication identifying a terminated state for the dialog, and further including a subscription state indication identifying a terminated subscription.

29-37. (Canceled).

38. (Previously presented) A system for communicating over an IP Multimedia core network Subsystem (IMS), comprising:

first and second User Equipments (UE) configured to engage in a dialog over the IMS;

a plurality of Call Session Control Functions (CSCF) associated with the IMS, comprising first and second Serving CSCFs (S-CSCF) and first and second Proxy CSCFs (P-CSCF);

wherein:

the first and second P-CSCFs serve as first points of communication within the IMS for the first and second UEs respectively, and are coupled to communicate with at least the first and second S-CSCFs respectively;

the first and second P-CSCFs are configured to subscribe to the first and second S-CSCFs respectively, and the first and second UEs are configured to subscribe to the second and first P-CSCFs respectively;

each of the CSCFs comprise a release recognition module configured to independently identify a release of the dialog, and a notification module to generate a release notification for transmission towards its respective subscriber; and

each of the UEs and CSCFs comprise a session release module configured to release the dialog in response to receiving the release notification.

39. (Original) The system as in Claim 38, wherein each of the first and second UEs is further configured to initiate a second release notification for transmission towards the other one of the first and second UEs to release the dialog, in response to receiving the release notification originating at one of the CSCFs.

40. (Canceled).

41. (Previously presented) A computer-readable medium having instructions stored thereon which are executable by a Call Session Control Function (CSCF) computer system for releasing a dialog established over an IP Multimedia core network Subsystem (IMS), the instructions executable by the CSCF computer system for performing steps comprising:

independently determining whether a session should be released at the CSCF;
accepting a subscription to a session release notification from a User Equipment (UE), wherein the session release notification includes a directive for the UE to release the session at the UE; and

generating the session release notification for transmission to the UE in response to the session being released at the CSCF.

42. (Original) The computer-readable medium as in Claim 41, wherein the instructions executable by the CSCF computer system further comprises instructions for performing steps comprising:

parsing second session release notifications received from a second CSCF associated with the session, and in response identifying an indication to release the session at the CSCF; and

releasing the session at the CSCF if the indication to release the session at the CSCF is identified.

43. (Original) The computer-readable medium as in Claim 41, wherein the instructions executable by the CSCF computer system further comprises instructions for performing steps comprising issuing a subscription request to a second CSCF associated with the session, wherein the subscription request comprises a request for session release notifications originating at the second CSCF associated with the session.